



**Afilli**  
Housekeeping and Hobby

## Afilli Multisurface Varnish

Afilli Multisurface Varnish is a glossy, transparent, water-based protective varnish developed to provide superior performance on all surfaces.



### THINNING

The product is ready-to-use. Recommended to be applied in minimum two coats according to the applied surface's condition and color used after thinning by maximum 5% by volume with clean water in brush, roller and sponge applications.

### DRYING TIME (@ 20°C, 65% RH):

Resting period between coats: 4 hours  
Final Dry: 24 hours Full  
Drying: 7 days (drying time may increase at higher relative humidity and lower temperature).

### CONSUMPTION

Depending on the type, absorbency and structure of the application surface, an area of 10-14 m<sup>2</sup> area can be painted in a single coat with 1 Liter. A controlled sample test should be performed prior to the final consumption.

### Airless Spraying

Pressure: 120-140 bars  
Nozzle angle: 50° Nozzle size (Inch): 0.019"  
Thinning: Ready to use. Recommended to be applied in one coat provided that the sufficient film thickness is achieved after thinning by 5% with clean water in airless spraying if needed.

### STORAGE

It can be stored in its unopened package for 3 years, in a cool and dry place, away from frost and direct sunlight. Close the lid air-tight immediately after application.

### PACKAGING

1 LT  
500 ml  
250 ml

### FEATURES

Can be used in interior and exterior spaces. Provides strong resistance to UV rays. Resistant to impacts. Moisture resistant. High water repellence. Does not affect the natural appearance of applied surface. Provides a glossy and smooth texture. Easy to apply. Does not leave brush or roller marks. Includes low VOC, harmless to health. Odorless. Compliant with EN 71-3 standards.

### APPLICATION SURFACES

Can be applied on surfaces such as wood, metal, glass, ceramic, plastic, stone, PVC, walls, cardboard and cloth.

### APPLICATION

Application surfaces should be clean. Should be cleaned from dirt and dust. Hardening and total clinging to surface is achieved in 7 days.

### WARNING-1

Ensure that the ambient and surface temperatures are between +5°C and +30°C throughout the application and drying out period of the product.